



MipCam Smartkameror		
Modeller	NKIP308-FHD	NKIP318-FHD
Point-to-Point	YES	YES
Outdoor IP66-rated	Indoor only	YES
IR cut filter	YES	YES
Viewing angle	Horizontal:60°, Vertical:45.0°	Horizontal:53.4°, Vertical:40.0°
LEDs	12	12
Aperture	F2.0	
Infrared Night Vision	YES	YES
Night Vision Distance	8-12m	15-20m
Focal length	f=3.6mm	f=4.3mm
Recording: SDcard / NAS cifs	Max128Gb YES	YES
Audio output(2 way audio)	YES	YES
Digital I/O	NO	YES
Dimensions(W x D x H mm)	62mmX95mmX34.8mm	φ70mmX190mm
Weight(Main Body)	85g	700g
Power requirements	DC 12V	
Power consumption	3.75W	
Image compression	H.264、MPEG-4、MJPEG	
Image resolution	1920x1080,1280x720(HD), 768x432, 512x288, 256x144, 176x144	
Max. frame rate	25fps @ 1920x1080	
Audio compression	AAC、AMR	
Built-in microphone	Electret Condenser Microphone	
Simultaneous viewers	16	
Authentication	ID/Password, Administrator/General User (Up to 64)	
Network protocols	TCP、UDP、IP、ARP、ICMP、DHCP、DNS、HTTP、FTP、SMTP、NTP、PPPoE、UPnP、DDNS	
Stream type	HTTP, RTSP/RTP/RTCP, 3GPP	
Network connection	Ethernet (10BASE-T/100BASE-TX)	
Wireless technology	IEEE802.11b/g/n	
Frequency	2.412-2.462GHz	
Transmission speed	150Mbps/54Mbps/11Mbps/5.5Mbps/2Mbps/1Mbps(Auto Switch)	
Security	WEP (64/128 bit)、WPA-PSK(AES/TKIP)、WPA2-PSK(AES/TKIP)	
Min.illumination	1.0 Lux	
Image device	1/4" CMOS	
Pixels	2 Mp (FHD)	
White Balance	Auto	
Exposure mode	Auto	
Gain	Auto	
Operating temperature	-5 to +45 °C (+22 to +113 °F)	-20 to +50°C(-4 to +122°F)
Storage temperature	-20 to +60 °C (-4 to +140 °F)	-20 to +60°C(-4 to +140°F)
Operating humidity	20 ~ 80%RH(Non-condensing)	20 ~ 90%RH(Non-condensing)
Storage humidity	20 ~ 95%RH(Non-condensing)	
Operating system	Windows2000, XP, VISTA, Windows7, Linux, Android, iPhone、windows Moblie、BlackBerry	
Processor	Intel Pentium III, 1GHz or Higher	
Memory	256MB RAM Minimum	
Web browser	Microsoft Internet Explorer Version 5.5 or Later Safari、Mozilla Firefox、Google Chrome and most other browsers	